## SCAN-415B Matrix

## For Wayne Kerr models 3255 and 3260









- ♦ Standard Model 415B with 15 kelvin measuring contacts
- ♦ Checking coils, coke, transformers or multi-pin PCBs or other DUT's
- ♦ Other models with 30 or more measurement points
- ♦ Supported the Wayne Kerr models 3255 and 3260
- ♦ Special relays with a tolerance of +/- 5mOhm
- ♦ Measurements LCR, Turn Ratio with winding test, delta and more
- ♦ Very high life expectancy and very high repeat accuracy
- ♦ Model 415B Open / Short calibration to 3 MHz
- ♦ USB interface control
- ♦ Hardware START and PASS/FAIL signal can be connected
- ♦ VG64 A-C kelvin pin connector, connector board or plug
- ♦ MESCO View Standard software, up to 25 test steps
- ♦ New Model 415B model replacing for 415T the already in use over 20 years
- ♦ Consideration of customer requirements is possible



Specification:

Relays: 2C Relay

Volt: to 500VDC, 3260 Option

Switching Current 1A

Strom 1ADC, 3255/3260 Option

Switching Time 1.5ms

Dimension: 28\*20\*8 cm Weight: 4 Kg **Tolerance from pin to pin** 

 $C \pm 50pF$   $L \pm 1\mu H$  $RDC \pm 100m\Omega$ 

**Repeat Measurement** 

RDC  $\pm$  5m $\Omega$ L  $\pm$  100nH Connections:

USB, Start input, PASS/FAIL output



**SET Skiba GmbH**, Hönnetalstr. 58, 58802 Balve Tel. 02375 9381464, Fax 02375 9381466, info@setskiba.de